

SAVIN

IM C3000

IM C3500

✓ Copier ✓ Printer ✓ Facsimile ✓ Scanner



11" x 17" Multifunction Color

Welcome to a new era of technology that keeps your workplace up-to-date, now and in the future. Smarter working made simple thanks to the SAVIN IM C3000/C3500.

It's time to:

- Protect your devices with easy access to security updates.
- Take advantage of easy productivity upgrades at your own pace.
- Save costs by bringing high-standard quality print output in-house.
- Maximize productivity with streamlined workflows.

Today's workplace needs to be ready for tomorrow. Intelligent Devices provide smooth access to functionality upgrades and productivity enhancements when they are released, without needing to change your hardware. Turn your device into a powerful hub that helps you manage information workflows efficiently, using technology that's scalable, secure, sustainable and simple.



Savin
Outstanding Achievement in Innovation for
Savin Intelligent Scanning

Get greater control of scan and print management:

- Scan small documents — with the small size paper scan unit.
- Improve scan accuracy — double feed detection unit.
- Enhance print management — with Color Controller E-25C.
- Produce professional grade flyers with inner multifolding unit.

Embrace lower running costs and reduced energy consumption thanks to environmentally friendly low TEC (Typical Electricity Consumption) values. Furthermore, take advantage of Intelligent Support services that anticipate potential issues and send corrective instructions via the Smart Operation Panel, avoiding interruptions and prolonging the optimal performance of your device — avoiding the need for intervention by more costly IT resources.

Our intelligent devices provide:

- Efficient working and reduced user intervention — by expanding paper capacity.
- Variable finishing and paper options — for a professional touch.
- A consistent user experience across your fleet.
- Maximum device uptime and minimal disruption with Intelligent Support.

Printing from 30 to 35 CPM, the SAVIN IM C3000/C3500 offer next-level productivity. Interact with the 10.1" Smart Operation Panel like a typical smart device and configure it for quick and easy access to apps you use most often. A variety of mobile connectivity options enable printing or scanning to the office network or cloud from a smart device, with built-in support for NFC, AirPrint® or Mopria. All this underpinned by a unique suite of support apps from SAVIN Smart Integration.



SAVIN IM C3000/IM C3500

MAIN SPECIFICATIONS

| IM C3000 | | IM C3500 | |
|--|--|----------|---------------------|
| GENERAL | | | |
| Warm-up time | | | 21 seconds |
| First output speed: B/W | | | 4.5 seconds |
| First output speed: full color | | | 6.9 seconds |
| Continuous output speed | 30 ppm | | 35 ppm |
| Memory: standard | | | 2 GB |
| Memory: maximum | | | 4 GB |
| HDD: standard | | | 320 GB |
| HDD: maximum | | | 320 GB |
| SPDF capacity | | | 220 sheets |
| Weight | 219.1 lbs / 99.3 kg | | 219.1 lbs / 99.3 kg |
| Dimensions: W x D x H | 587 x 685 x 963mm, 23" x 27" x 37.9" | | |
| Power source | 120V - 127V 60Hz | | |
| COPIER (STANDARD) | | | |
| Multiple copying | Up to 999 copies | | |
| Resolution | 600 dpi | | |
| Zoom | From 25% to 400% in 1% steps | | |
| PRINTER (STANDARD) | | | |
| CPU | Intel Apollo Lake 1.3GHz | | |
| Printer language: standard | PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation) | | |
| Printer language: option | Genuine Adobe® PostScript® 3™, PDF Direct from Adobe® | | |
| Print resolution | Up to 1,200 x 1,200 dpi | | |
| Network interface: standard | Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B | | |
| Network interface: option | Wireless LAN (IEEE 802.11a/b/g/n), Additional NIC (2nd port) | | |
| Mobile printing capability | Apple AirPrint®, Mopria, Google Cloud Print, NFC, Ricoh Smart Device Connector | | |
| Windows® environments | Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012R2, Windows® Server 2016 | | |
| Mac OS environments | Macintosh OS X v10.11 or later | | |
| UNIX environments | UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX | | |
| SAP® environments | SAP® R/3®, S/4® | | |
| Other supported environments | IBM iSeries AS/400 using OS/400 Host Print Transform | | |
| SCANNER (STANDARD) | | | |
| Scanning speed | 120 ipm (simplex)/240 ipm (duplex) | | |
| Resolution: maximum | Up to 1,200 dpi | | |
| Compression method | TIFF (MH, MR, MMR, JBIG2), Grayscale | | |
| File formats | Single Page: TIFF, JPEG, PDF, PDF/A, High Compression PDF, encryption PDF, OCR* Multi Page: TIFF, PDF (Default), PDF/A, High Compression PDF, encryption PDF, OCR* * Requires optional OCR Unit Type M13 | | |
| Scan modes | E-mail, Folder, USB, SD Card | | |
| FACSIMILE (OPTIONAL) | | | |
| Circuit | PSTN, PBX | | |
| Transmission speed | 2 seconds (200 x 100 dpi, JBIG, ITUT #1 chart TTI off, memory transmission) | | |
| Modem speed: maximum | 33.6 Kbps | | |
| Resolution: standard | 8 x 3.85 line/mm, 200 x 100 dpi | | |
| Resolution: option | 16 x 15.4 line/mm, 400 x 400 dpi | | |
| Compression method | MH, MR, MMR, JBIG | | |
| Scanning speed | 81 spm (A4/LT LEF Image Rotation) | | |
| Memory: standard | 4 MB (320 pages) | | |
| Memory: maximum | 60 MB (4,800 pages) | | |
| PAPER HANDLING | | | |
| Recommended paper size | Tray 1: 8-1/2" x 11" (A4); Tray 2: 5-1/2" x 8" - 12" x 18" (SRA3, A3 - A6, B4 - B6), Envelopes Bypass tray: Up to 12" x 18", Envelopes, Custom Sizes [Width: 3.5" - 12.6" (90 - 320 mm), Length: 5.8" - 49.6" (148 - 1260 mm)] | | |
| Paper input: standard | 1,200 sheets | | |
| Paper input: maximum | 4,700 sheets | | |
| Paper output: standard | 500 sheets 8.5" x 11" (A4) or smaller; 250 sheets (B4) or larger | | |
| Paper output: maximum | 1,625 sheets | | |
| Paper weight | Trays: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m²) Bypass: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m²) Duplex: 14 - 68 lb. Bond/142 lb. Index (52 - 256g/m²) | | |
| Paper types | Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-printed, Bond, Coated, Envelope, Label, OHP, Gloss | | |
| ECOLOGY | | | |
| Power consumption: maximum | Less than 1,584 W | | |
| Power consumption operation: B/W | 507.7 W | | 533.6 W |
| Power consumption operation: full color | 560.8 W | | 600.3 W |
| Power consumption: ready | 47.7 W | | |
| Power consumption: sleep | 0.53 W | | |
| TEC¹ | 0.35 kWh | | 0.39 kWh |
| ENERGY STAR® | Certified | | |
| EPEAT® | Gold Rated* | | |
| * EPEAT Gold rating is applicable only in the USA. | | | |

¹ TEC value is measured based on the ENERGY STAR Ver. 3.0 test method.

SAVIN IM C3000/IM C3500

MAIN SPECIFICATIONS

IM C3000

IM C3500

OUTPUT TRAYS AND FINISHER OPTIONS

| | |
|--|--|
| 1 x 550-sheet Paper Tray (PB3270) | Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m ²) |
| 2 x 550-sheet Paper Tray (PB3280) | Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m ²) |
| 2,000-sheet Large Capacity Tray (LCIT PB3290) | Paper size: 8.5" x 11" (A4), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m ²) |
| 1,500-sheet Side Large Capacity Tray (LCIT RT3040) | Paper size: 8.5" x 11" (A4, B5), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m ²) |
| 1,000-sheet Hybrid Finisher (SR3260) | Paper size: Proof Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Shift Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²); Staple capacity: 50 sheets; Staple paper size: 8.5" x 11" to 12" x 18" (A4 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m ²); Staple positions: Top, Bottom, 2 staples |
| 1,000-sheet Booklet Finisher (SR3270) | Paper size: Proof Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Shift Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Booklet Tray: 8.5" x 11" to 12" x 18" (A4 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²); Stack capacity: 1,000 sheets; Staple capacity: 50 sheets; Staple paper size: Normal Staple: 8.5" x 11" to 12x18" (A4 - A3); Saddle Stitch: 8.5" x 11" to 12" x 18" (A4 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m ²); Staple positions: Top, Bottom, 2 staples, Booklet |
| 250-sheet Internal Finisher (SR3300) | Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²), Stack capacity: 250 sheets, Staple capacity: 5 sheets, Staple paper size: 7.25" x 10.5" to 11" x 17" (B5 - A3), Staple paper weight: 17 - 21 lb. Bond (64 - 80 g/m ²), Staple positions: Top |
| 500-sheet Internal Finisher (SR3250) | Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²); Stack capacity: 500 sheets; Staple capacity: 50 sheets; Staple paper size: 7.25" x 10.5" to 11" x 17" (B5 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m ²); Staple positions: Top, Bottom, 2 staples |
| Internal Shift Tray (SH3080) | Tray capacity: 250 sheets with 80 g/m ² paper (A4, LT or smaller); 125 sheets with 80g/m ² paper (B4, LG or larger); Paper size: 12.60" x 23.62" or smaller; Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²) |
| One-bin Tray (BN3130) | Tray capacity: 125 sheets, Paper size: 5.5" x 8.5" to 12" x 18" (A5-A3), Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m ²) |
| Internal Multi-fold Unit (FD3010) | When External Finisher is attached: A3 - A6 SEF, DLT - HLT, 12.6" x 17.7", 12" x 18" Z folding: A3, B4, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) Half-folding: A3, B4, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio), 12" x 18", 12.6" x 17.7" (SRA3) Inner three-folding: A3, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) When External Finisher is not attached: A3 - A6 SEF, DLT - HLT Z folding: A3, B4, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) Half-folding: A3, B4, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) Inner three-folding: A3, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) Outer three-folding: A3, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) Paper Weights for Folding: 20 - 28 lb. Bond/58 lb. Index (64 - 105 g/m ²) Stack Capacity: Folded: 20 sheets Unfolded: 100 sheets |

OTHER OPTIONS

Fax Option Type M37, G3 Interface Unit Type M37, Memory Unit Type M37 4GB, Cabinet Type F, Caster Table Type M3, VM CARD Type M37, Punch units (PU3070, PU3080), PostScript3 Unit Type M37, IEEE 802.11 a/g/n Interface Unit Type M19, Device Server Option Type M37, File Format Converter Type M19, OCR Unit Type M13, Small Paper Feeding Unit Type M37, Page Keeper Type M37, Imageable Area Extension Unit Type M19, External Keyboard Bracket Type M19, Optional Counter Interface Unit Type M12, Key Counter Bracket Type M3, NFC Card Reader Type M37, Smart Card Reader Built-in Unit Type M37, ESP XG-PCS-15D, External USB Keyboard (No Bracket), EFI Impose Type FS150, EFI Compose Type FS150, Hot Folders Type FS-100, Spot On Type FS100, Auto Trap Type FS-100, Fiery CPS v4, Fiery ES-2000 Spectrophotometer, EFI Productivity Pack for Fiery E22b E22c, FAX Memory Unit Type M19 64MB, Bridge Unit BU3090, Color Controller E-25C, Banner Paper Guide Tray Type M19

CONSUMABLES

| | |
|----------------------------|---------------|
| Toner: black | 31,000 prints |
| Toner: cyan/magenta/yellow | 19,000 prints |

Consumable yield measuring method based on A4, 5% coverage

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Savin parts and supplies.

Some features may require additional options and/or charges.

Ricoh USA, Inc.

300 Eagleview Boulevard
Exton, PA 19341



1-877-472-8460



www.savin.com

